

Headlok® Security Head Screws

Headlok® Security Head Screws are designed for securely fastening both metal roofing and cladding profiles, on buildings where the prevention of unauthorised entry and safeguarding of property is of paramount importance e.g. warehouses and government and defence installations.

Features

- Unique Tamper-proof head design.
- The screws can be installed or undone by using the Buildex® Security Head Socket. Each socket is engraved with its own ID number which corresponds to a registration card that is recorded in a database. This allows for traceability and auditing purposes.
- Climaseal® 4 coated
- HiGrip® design which prevents water entry through roof sheeting (not available in 25mm length screw)
- Available with either Teks® or Zips® drill point
- ShankGuard® design for protection from scratching and scouring during installation as well as increasing corrosion protection.
- Head can be painted to match popular roofing and cladding colour range



With Seal - Teks Point



Application: For valley fixing corrugated, square rib roofing and cladding profiles to steel purlins and metal battens.



Application: For crest fixing corrugated and square rib roofing profiles to steel purlins up to 4.5mm thick (2.4mm lapped purlins), in high wind and cyclonic regions.

Gauge	T.P.I	Length	Pack
M14	10	25	500
M14	10	50	1000

HiGrip® with Seal - ZIPS Point



Application: For crest fixing corrugated roofing profiles to timber, thin metal battens and steel purlins up to 1.9mm thick & square rib roofing profiles to thin metal battens.

Gauge	T.P.I	Length	Pack
M6	11	50	1000

Metroll Newcastle

ABN 97 001 446 439
 268 Macquarie Road
 WARNERS BAY NSW 2282
 AUSTRALIA
 P: +61 (0)2 4954 5799
 F: +61 (0)2 4954 0891
sales@metrollnewcastle.com.au
www.metrollnewcastle.com.au